

MODEL CODE		S5000		S7500	S10000	S12000
		PD452MHI004	PD402MNI002	PD722MHB002	PD952MHB001	PD113MHB001
SINGLE-PHASE POWER						
Power Continuous/Max	kW	4.1/5.0		6.1/7.2	8.8/9.5	10.2/12.0
Voltage	Volt	120/240		120/240	120/240	120/240
Frequency	Hz	60		60	60	60
Power Factor	cosfi	1		1	1	1
ENGINE						
Brand		Honda	Robin Subaru	Honda	Honda	Honda
Model		GX270	EX27	GX390	GX610	GX620
Displacement	cc	270	265	389	614	614
Cycle		4	4	4	4	4
Power	kW(HP)	6.6(9)	6.6(9)	9.6(13)	13.2(18)	14.7(20)
Fuel		Gasoline	Gasoline	Gasoline	Gasoline	Gasoline
Aspiration		Natural	Natural	Natural	Natural	Natural
Cooling system		Air	Air	Air	Air	Air
Starting system		Recoil	Recoil	Electric/Recoil	Electric	Electric
CONSUMPTION						
Consumption	lb(g)/Kw/h	0.69(313)	0.79(360)	0.69(313)	0.69(313)	0.69(313)
Consumption at 75%	gal(l)/h	0.45(1.7)	0.51(1.95)	0.66(2.5)	0.89(3.4)	1(3.8)
Tank capacity	gal(l)	7.9(30)	7.9(30)	7.9(30)	7.9(30)	7.9(30)
Running time at 75%	h	17.5	15.4	12.1	8.8	7.9
DIMENSIONS AND WEIGHT						
Length	in(mm)	29.5(749)		31(787)	32(813)	32(813)
Width	in(mm)	22.2(565)		22.2(565)	23(584)	23(584)
Height	in(mm)	22.4(569)		22.4(569)	27(686)	27(686)
Weight (dry)	lb(kg)	157(71)		200(91)	265(120)	275(125)
STANDARD EQUIPMENT						
Circuit Breaker Protection		●	●	●	●	●
Oil-guard system		●	●	●	●	●
Hourmeter		●	●	●	●	●
Voltmeter		●	●	●	●	●
DPLX 125V-20A (5-20R) socket		1		1	1	1
DPLX GFCI 125V-20 (5-20R) socket		1	2	1	1	1
TL 125/250V-20A (L14-20R) socket		1	1			
TL 125/250V-30A (L14-30R) socket				1	1	1
TL 250V-20A (L6-20R) socket		1	1			
TL 250V-30A (L6-30R) socket				1		
125/250V-50A (14-50R) socket					1	1
ACCESSORIES						
Wheels & Handles		●	Std	●	●	●
Lifting Kit		●	●	●	●	●
Cover		●	●	●	●	●
Transfer Switch		●	●	●	●	●
Generator Cover		●	●	●	●	●