

UNIT SPECIFICATIONS

DC Voltage	CC: 26.8 V	
DC Current	CC: 180A	
Current Range	50-180 A	
Max Duty Cycle w/ Full Amps Available	50% @180 A	
Welding Processes	SMAW FCAW GTAW ACAC	
Fuel Tank Capacity	3.7 gal	16.8 L
Fuel Consumption at Rated Load	0.93 gph	

DIMENSIONS & WEIGHTS

Overall Length	27.5 in	69.85 cm
Overall Width	22 in	55.88 cm
Overall Height	23.75 in	60.3 cm
Shipping Dimensions	28.5 x 23 x 28 in 72.4 x 58.4 x 71.1 cm	
Operating Weight	225 lb	102.3 kg
Shipping Weight	239 lb	108.6 kg

GENERATOR FEATURES

AC Power Output (Single Phase)	3 kW
Cycle	60 Hz
Voltage	120 V
Amperage	25 A
Voltage Regulation	3 %
Receptacles	NEMA 5-20R 125V GFCI 20A NEMA L5-30R 125V Twist-Lock 30A

GENERAL FEATURES & OPTIONS

AC/DC Simultaneous Use	Standard
Lifting Bale	Standard
Automatic Safety Shutdown	Oil Level
Idle Switch	Standard
Optional Wheel Kit	UWK