

Easy-Rooter™

A heavy duty machine for 3" thru 10" lines

The Easy Rooter is a tough, easy-to-use machine. It has a rugged powder coated steel frame with roll bars to protect the motor and heavy-duty roller bearings in the cage for longer life and greater motor efficiency on long runs. The large zinc-plated cage holds 100 feet of 3/4" or 5/8" Flexicore cable, while optional smaller cage holds 100 feet of 1/2" cable.

An extra-long plated folding handle quickly locks in place, making it much easier to wheel the Easy Rooter to the job, without sacrificing the compact size needed for easy loading in a car trunk.

The Easy Rooter rolls smoothly on big 10" ball bearing wheels mounted on a half inch reinforced axle. Power is supplied by a 1/3 hp motor with capacitor start, thermal overload protection, and reverse switch. Standard safety features include an air-actuated foot pedal, ground fault circuit interrupter, and safety slip clutch.



SPECIFICATIONS:

Weight: 80 lbs. without cable.

Large Cage: Zinc plated. 100 ft. of 3/4" capacity with heavy duty roller bearings.

Small Cage: 100 ft. of 1/2" capacity with oilite bronze bushings.

Motor: 1/3 hp heavy duty, capacitor start, thermal overload protection, Forward/Off/Reverse Switch.

Safety Slip Clutch: Protects cable and operator.

Foot Pedal: Leaves operator's hands free to control cable. Uses air pressure, so there's no electrical contact between pedal and motor.

Power Cord: 20 ft. 3 wire vinyl covered with molded plug. Equipped with ground fault circuit interrupter.

Wheels: 10" semi-pneumatic with roller bearings.

Cables: 3/4" for 4-10" lines; 5/8" for 3-6" lines; 1/2" for 2-3" lines and 4" lines without roots.

Cutter Set: Spear Head, 2" U-Cutter, 3" Heavy-Duty Side Cutter, 3" Heavy-Duty Saw Blade and Large Retriever. On units with 1/2" cable, Arrow Head, 1 1/2" U-Cutter and Small Retriever also included. Others available.

Leather Gloves: With reinforced palm for hand protection.

How-To Video included.

FLEXICORE®CABLE

