Technical Information for GA97HE Generator

The generator for the toughest jobs. This delivers enough power to run a variety of tools and

RECEPTACLES & CIRCUIT

equipment. Powered by a twin-cylinder engine with electric start, and recoil backup, it offers up to 10 hours of continuous run time.

- Twin duplex receptacles and three twist-lock receptacles for job site versatility
- 100% copper windings for maximum conductivity
- · Alternator design eliminates maintenance by removing brushes and slip rings
- Heavy-duty 1-inch (25 mm) steel pipe frame and shock mounts protect the generator
- · Includes folding lifting bale as standard equipment

Powered by a twin-cylinder 18-hp Honda engine with low-oil shutdown, automatic idle control.

| UNIT SPECIFICATIONS | | | DIMENSIONS & WEIGHTS | | |
|-----------------------|--------------|------------------|----------------------|-----------------|-----------|
| Alternator Design | Brushless | | Overall Length | 31.25 in | 79.375 cm |
| | | | Overall Width | 21.25 in | 53.975 cm |
| Frequency | 60 hz | | Overall Height | 28.5 in | 72.39 cm |
| Phase | Single Phase | | Shipping 32 x 22.5 | | x 31.5 in |
| Voltage | 120/240 V | | Dimensions | 81 x 56 x 91 cm | |
| Sound level at | 78 dBA | Operating Weight | 327 lb | 148.3 kg | |
| 30 ft | മയന | | Shipping Weight | 342 lb | 155 kg |
| Fuel Tank Capacity | 10 gal | 37.8 L | , | | 33354343 |

| | | | BREAKERS | | |
|------------------|-------------------|----------------------|-------------------------|--|--|
| | | | Main Circuit Breaker | 35 A | |
| POWER GENERATION | | | Number of Poles | 2 | |
| Watts | Maximum 9700 W | Continuous 8400 W | | 5-20R 125V GRCI 20A L5-20R 125V T-Lock 20A | |
| Amps at 120V | A 8.08 | 70 A | 1 Receptable of | | |
| Amps at 240V | 40.4 A | 35 A | Each: | L5-30R 125V T-Lock 30A L14-30R 125/250V T- Lock 30A | |

OPTIONS & ACCESSORIES

This model is equiped with a Full Power Switch

Optional Wheel Kit WKT-97