

Specifications

Model#	Rating	Amperage	No Load RPM	Max. Tool HP	Blade Diameter (in.)	Arbor Size	Height (in.)	Weight (lbs.)	Bevel Angle Range	Bevel Detents	Miter Angle Range	Miter Detents	Crown Molding - Angled Against Fence	Crown Molding - Laying Flat	Base Molding - Angled Against Fence	Miter/Bevel (Max Height x Width)
5412	120V	15	3,800	3.0	12"	1"	20	59	47° left & 47° right	33.9° left with positive stops at 0° and 45°	52° Left / 60° Right	0°, 15°, 22.5°, 31.6°, 45° (Left/Right) 60° (Right)	6"	10-1/4" (31.6° miter and 33.9° bevel)	4-1/4"	0°/0° - 4-1/4" x 12-1/2" (4 x 12 Nominal) 0°/45° right - 1-3/4" x 12-1/2" (2 x 12 Nominal) 0°/45° left - 2-3/4" x 12-1/2" (2 x 12 Nominal) 45°/0° - 4-1/4" x 8-3/4" (4 x 8 Nominal) 45°/45° right - 2-5/8" x 8-3/4" (2 x 8 Nominal) 45°/45° left - 2-3/4" x 8-3/4" (2 x 8 Nominal)
4410	120V	15	4,800	3.0	10"	5/8"	19	55	47° left & 47° right	33.9° left with positive stops at 0° and 45°	52° Left / 60° Right	0°, 15°, 22.5°, 31.6°, 45° (Left/Right) 60° (Right)	6"	10-1/4" (31.6° miter and 33.9° bevel)	4-1/4"	0°/0° - 3-5/8" x 12-1/4" (4 x 12 Nominal) 45°/0° - 3-5/8" x 8-3/4" (4 x 8 Nominal) 45°/45° - 2-1/4" x 8-3/4" (2 x 8 Nominal) 45°/45° right - 1-1/4" x 8-3/4" (2 x 8 Nominal)